

AC Level 2 70A SINGLE PORT CHARGING STATION (PEDESTAL)

MODEL	SINGLE PORT 70A	
	MODEL Number	EVP-2001-70-P-0001
	PRODUCT Number	L2P-70-240-16-001
Power per Port	16.8 kW (240 VAC @ 70A)	
ELECTRICAL SERVICE		
Power	240/208 VAC, 70A Load with 100A Branch Circuit Per Port	
Service Panel	100A Breakers per Port (No GFCI)	
Service Wiring	3-Wire (L1, L2, Earth Ground)	
FUNCTIONAL INTERFACES		
Connector Type	SAE J1772	
Charging Protocol	SAE J1772	
Standard Cable Length	25 ft	
Cable Retractor	Optional (Cable 18 ft w/ Cable Management)	
LCD Display	500 Nits, 7" Color, 800 x 480, UV Protected	
Card Reader	ISO 14443 Type A & B, ISO 18092 NFC	
SAFETY AND CONNECTIVITY		
Ground Fault Detection	20 mA	
Plug-Out Detection	SAE J1772	
Power Measurement (opt)	Accuracy: 1% - 5%	
Power Report Interval	Every 15 minute on the hour	
Wireless	2.4 GHz Wi-Fi (802.11 b/g/n)	
Wide Area Network	4G Modem	
Communication Protocols	OCPP 1.5 and 1.6 Compliant	
SAFETY AND OPERATION		
Enclosure Rating	NEMA 3R	
Regulatory Compliance	ETL Certified for USA and cUL Certified for Canada; Complies with UL 2594, UL 2231-1, UL 2231-2, and NEC Article 625, EMC: FCC Part 15 Class A	
Operating Temperature	-30°C to +60°C (-22°F to 140°F)	
Storage Temperature	-50°C to +80°C (-58°F to 176°F)	
Humidity	95% Non-Condensing	



- ▶ SINGLE PORT 70A LEVEL 2
- ▶ CHARGING PROTOCOL: SAE J1772
- ▶ 16.8 KW PER PORT
- ▶ 25 FT or 18 FT with CABLE RETRACTOR
- ▶ NEMA 3R HOUSING
- ▶ RFID READER
- ▶ OCPP COMPLIANT – STANDARD
- ▶ 7" COLOR SCREEN – STANDARD
- ▶ UL COMPLIANT – ETL CERTIFIED
- ▶ OPTIONS:
 - CABLE RETRACTOR
 - CREDIT CARD READER
 - CREDIT CARD SCANNER

BTC POWER

1719 S Grand Ave, Santa Ana, CA 92705

www.btcpower.com

sales@btcpower.com