

Modular HPC System: 100, 150, 200, 350 kW

PARAMETERS	POWER ENGINE CABINET MODEL					
	MODEL Number					
	EVPC-200-2-480					
	PRODUCT Number					
	HPCT-100-480-2	HPCT-150-480-2	HPCT-200-480-2	HPCT-200-480-2		
Power Rating	100 kW	150 kW	200 kW	350 kW (two 200kW power cabinets connected in parallel to add up power output from both units)		
Number of Power Engines	2	3	4	8 (4 from each power cabinet)		
Input Power	480VAC-3P@132A	480VAC-3P@198A	480VAC-3P@264A	480VAC-3P@264A		
Input Power AC Current (FLA)	132 A	198 A	264 A	2 x 264 A		
Power Stage Efficiency Rating	> 92% (Full Load)					
Max. Out DC Current up to 920 VDC	108 A	162 A	216 A	432 A		
Max. Out DC Current up to 500 VDC	250 A	375 A	500 A	500 A		
Max. Output DC Voltage	50 - 950 VDC					
Max # of Dispensers	2	2	2	2		
Dimension & Weight	42"W x 35"D x 82"H, 1900 lbs					

PARAMETERS	DISPENSER MODEL					
	MODEL Number					
	EVDSP-50-5-120-0-2-C-4-0		EVDSP-350-5-120-0-2-C-4-0		EVDSP-350-5-120-0-2-C-4-0	
	PRODUCT Number					
	HPCD1-125		HPCD1-200		HPCD1-350	
Connectors	SAE CCS1	CHAdEMO	SAE CCS1	CHAdEMO	SAE CCS1 (Liquid Cooled)	CHAdEMO
Rated Output Current	125 A	125 A	200 A	200 A	350 A	200 A
Max DC Voltage (VDC)	500 V	500 V	950 V	500 V	950 V	500 V
Output Power	50 kW max		200 kW max		350 kW max	
Input Power (Auxiliary)	120 VAC					
Input Current (Auxiliary)	10 A FLA				21 A FLA	
Breaker Size	20 A				30 A	
Network	OCPP 1.5/1.6, BTCP Network					
Dimension & Weight	22"W x 15"D x 97"H, 600 lbs					

ENVIRONMENTAL AND COMPLIANCE (SYSTEM)	
Ambient Condition	-30 °C to +50 °C, 95% Humidity, 6000 ft Altitude. NEMA 3R
Safety Compliance	ETL Listed for USA and Canada: Complies with UL 2202, UL 2231, UL50E, NEC Article 625, CSA STD C22.2 No. 107.1 FCC Part 15 Class A

▶ STANDARD

- ▶ Dynamic Power Allocation in 50kW increments
- ▶ System available in 1 or 2-dispenser configuration
- ▶ Payment types: CC, RFID (OCPP Network Enabled)
- ▶ 15" Outdoor Color Display
- ▶ Connector Configuration:
 - SAE J1772 Combo CCS1 and CHAdEMO

▶ OPTIONAL

- ▶ ISO 15118:2014
- ▶ Customizable Backlit Acrylic Topper
- ▶ Apple & Android Pay (based on network provider)
- ▶ Connector Configurations:
 - Dual SAE J1772 Combo CCS1
 - Single CHAdEMO
 - Single SAE J1772 Combo CCS1



BTC POWER

1719 S Grand Ave, Santa Ana, CA 92705

www.btcpower.com

sales@btcpower.com